

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Part B - Superfast 47140

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Function or use category : Adhesive for equine hooves

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Royal Kerckhaert Horseshoe Factory
Rapenburg 76
4581AE Vogelwaard
The Netherlands
Info@vettec.com

1.4. Emergency telephone number

+31 114 671 361 (8 a.m. to 5 p.m., Monday to Friday) (Languages: Dutch, English, French, Italian, German and Portuguese)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

Signal word (CLP) : Warning
Contains : m-Phenylenebis(methylamine)
Hazard statements (CLP) : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
Precautionary statements (CLP) : P261 - Avoid breathing vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.3. Other hazards

other hazards which do not result in classification : Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
N,N,N',N'-Tetrakis(2-hydroxypropyl)ethylenediamine	CAS-No.: 102-60-3 EC-No.: 203-041-4 REACH-no: Not available	10 - 20	Eye Irrit. 2, H319
m-Phenylenebis(methylamine)	CAS-No.: 1477-55-0 EC-No.: 216-032-5 REACH-no: Not available	1 - 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/Kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=1.5 mg/l) Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
Methyloxirane substance listed as REACH Candidate (Methyloxirane (Propylene oxide)) substance with a Community workplace exposure limit	CAS-No.: 75-56-9 EC-No.: 200-879-2 EC Index-No.: 603-055-00-4 REACH-no: Not available	x < 0.0006	Flam. Liq. 1, H224 Carc. 1B, H350 Muta. 1B, H340 Acute Tox. 3 (Inhalation), H331 (ATE =0.5 mg/L) Acute Tox. 3 (Dermal), H311 (ATE = 300 mg/kg) Acute Tox. 4 (Oral), H302 (ATE=500 mg/Kg bodyweight) STOT SE 3, H335 Eye Irrit. 2, H319

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protective equipment for firefighters : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible materials : Strong acids. Strong oxidizing agents.

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Isopropyl Alcohol (67-63-0)	
Belgium - Occupational Exposure Limits	
Local name	Alcool isopropylique # Isopropylalcohol
OEL TWA	500 mg/m ³
OEL TWA [ppm]	200 ppm
OEL STEL	1000 mg/m ³
OEL STEL [ppm]	400 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
Bulgaria - Occupational Exposure Limits	
Local name	Изопропилов алкохол
OEL TWA	980 mg/m ³
OEL STEL	1225 mg/m ³
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.5 от 17 Януари 2020 г.)
Croatia - Occupational Exposure Limits	
Local name	Propan-2-ol; izopropil-alkohol; izopropanol
GVI (OEL TWA) [1]	999 mg/m ³
GVI (OEL TWA) [2]	400 ppm
KGVI (OEL STEL)	1250 mg/m ³
KGVI (OEL STEL) [ppm]	500 ppm
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 1/2021)
Croatia - Biological limit values	
Local name	Propan-2-ol
BLV	50 mg/l Karakteristični pokazatelj: aceton - Biološki uzorak: krv - Vrijeme uzorkovanja: na kraju radne smjene 0.86 µmol/l Karakteristični pokazatelj: aceton - Biološki uzorak: krv - Vrijeme uzorkovanja: na kraju radne smjene 50 mg/l Karakteristični pokazatelj: aceton - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 0.86 µmol/l Karakteristični pokazatelj: aceton - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
Czech Republic - Occupational Exposure Limits	
Local name	2-Propanol (Isopropanol; Izopropylalkohol)
PEL (OEL TWA)	500 mg/m ³

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isopropyl Alcohol (67-63-0)	
PEL (OEL TWA) [ppm]	200 ppm
NPK-P (OEL C)	1000 mg/m ³
NPK-P (OEL C) [ppm]	400 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	Isopropylalkohol (Isopropanol; 2-Propanol; sec-Propylalkohol)
OEL TWA [1]	490 mg/m ³
OEL TWA [2]	200 ppm
Regulatory reference	BEK nr 1426 af 28. juni 2021
Estonia - Occupational Exposure Limits	
Local name	2-propanool (isopropüülalkohol, isopropanool)
OEL TWA	350 mg/m ³
OEL TWA [ppm]	150 ppm
OEL STEL	600 mg/m ³
OEL STEL [ppm]	250 ppm
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
Finland - Occupational Exposure Limits	
Local name	2-Propanoli
HTP (OEL TWA) [1]	500 mg/m ³
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	620 mg/m ³
HTP (OEL STEL) [ppm]	250 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Alcool isopropylique
VLE (OEL C/STEL)	980 mg/m ³
VLE (OEL C/STEL) [ppm]	400 ppm
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Propan-2-ol
AGW (OEL TWA) [1]	500 mg/m ³
AGW (OEL TWA) [2]	200 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isopropyl Alcohol (67-63-0)	
Germany - Biological limit values (TRGS 903)	
Local name	Propan-2-ol
Biological limit value	25 mg/l Parameter: Aceton - Untersuchungsmaterial: B = Vollblut, U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2012 DFG 25 mg/l Parameter: Aceton - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende - Festlegung/Begründung: 11/2012 DFG
Regulatory reference	TRGS 903
Greece - Occupational Exposure Limits	
Local name	Ισοπροπυλική αλκοόλη
OEL TWA	980 mg/m ³
OEL TWA [ppm]	400 ppm
OEL STEL	1225 mg/m ³
OEL STEL [ppm]	500 ppm
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	IZOPROPIL-ALKOHOL
AK (OEL TWA)	500 mg/m ³
CK (OEL STEL)	1000 mg/m ³
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Hungary - Biological Exposure Indices	
Local name	Izopropil-alkohol (2-Propanol)
BEI	25 mg/l Biológiai expozíciós (hatás) mutató: acetone - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) 430 µmol/l Biológiai expozíciós (hatás) mutató: acetone - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén)
Remark	A foglalkozási vegyi expozíció esetén ajánlott biológiai expozíciós és hatásmutatók határértékei
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Isopropyl alcohol [Propan-2-ol]
OEL TWA [2]	200 ppm
OEL STEL [ppm]	400 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	2-Propanol
BLV	40 mg/l Parameter: acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B (Background), Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isopropyl Alcohol (67-63-0)	
Latvia - Occupational Exposure Limits	
Local name	Izopropanols (2-propanols, izopropilspirts, 1-metil-1-etanols)
OEL TWA	350 mg/m ³
OEL STEL	600 mg/m ³
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325 (Grozījumi Ministru kabineta 2011. gada 1. februārī noteikumiem Nr. 92)
Lithuania - Occupational Exposure Limits	
Local name	2-propanolis (izopropanolis, izopropilo alkoholis)
IPRV (OEL TWA)	350 mg/m ³
IPRV (OEL TWA) [ppm]	150 ppm
TPRV (OEL STEL)	600 mg/m ³
TPRV (OEL STEL) [ppm]	250 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Poland - Occupational Exposure Limits	
Local name	Propan-2-ol (izopropylowy alkohol)
NDS (OEL TWA)	900 mg/m ³
NDSch (OEL STEL)	1200 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	2-Propanol (isopropanol ou álcool isopropílico)
OEL TWA [ppm]	200 ppm
OEL STEL [ppm]	400 ppm
Remark	A4 (Agente não classificável como carcinogénico no Homem); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Portugal - Biological Exposure Indices	
Local name	2-Propanol
BEI	40 mg/l Parâmetro: Acetona - Meio: urina - Momento da amostragem: Fim do turno no fim da semana de trabalho - Notação: Vb (Valor basal), Ne (Não específico)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Alcool izopropilic/2-Propanol
OEL TWA	200 mg/m ³
OEL TWA [ppm]	81 ppm
OEL STEL	500 mg/m ³
OEL STEL [ppm]	203 ppm
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Romania - Biological limit values	
Local name	Alcool izopropilic

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isopropyl Alcohol (67-63-0)	
BLV	50 mg/l Indicador biologic: Acetonă - Material biologic: urină - Momentul recoltarii: sfârșit de schimb
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)
Slovakia - Occupational Exposure Limits	
Local name	Izopropylalkohol (propán-2-ol)
NPHV (OEL TWA) [1]	500 mg/m ³
NPHV (OEL TWA) [2]	200 ppm
NPHV (OEL STEL)	1000 mg/m ³
NPHV (OEL STEL) [ppm]	400 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	propan-2-ol (izopropilalkohol; izopropanol)
OEL TWA	500 mg/m ³
OEL TWA [ppm]	200 ppm
OEL STEL	1000 mg/m ³
OEL STEL [ppm]	400 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	2-propanol
BLV	25 mg/l Parameter: aceton - Biološki vzorec: kri - Čas vzorčenja: ob koncu delovne izmene 25 mg/l Parameter: aceton - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Isopropanol (Alcohol isopropílico)
VLA-ED (OEL TWA) [1]	500 mg/m ³
VLA-ED (OEL TWA) [2]	200 ppm
VLA-EC (OEL STEL)	1000 mg/m ³
VLA-EC (OEL STEL) [ppm]	400 ppm
Remark	VLB® (Agente químico que tiene Valor Límite Biológico), s (Esta sustancia tiene prohibida total o parcialmente su comercialización y uso como fitosanitario y/o como biocida. Para una información detallada acerca de las prohibiciones consúltase: Base de datos de productos biocidas: http://www.msssi.gob.es/ciudadanos/productos.do?tipo=plaguicidas Base de datos de productos fitosanitarios http://www.magrama.gob.es/agricultura/pags/fitos/registro/fichas/pdf/Lista_sa.pdf).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Spain - Biological limit values	
Local name	Isopropanol (Alcohol isopropílico)

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isopropyl Alcohol (67-63-0)	
BLV	40 mg/l Parámetro: Acetona - Medio: Orina - Momento de muestreo: Final de la semana laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Sweden - Occupational Exposure Limits	
Local name	Isopropanol
NGV (OEL TWA)	350 mg/m ³
NGV (OEL TWA) [ppm]	150 ppm
KTV (OEL STEL)	600 mg/m ³
KTV (OEL STEL) [ppm]	250 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Propan-2-ol
WEL TWA (OEL TWA) [1]	999 mg/m ³
WEL TWA (OEL TWA) [2]	400 ppm
WEL STEL (OEL STEL)	1250 mg/m ³
WEL STEL (OEL STEL) [ppm]	500 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Propanol
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	400 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	2-PROPANOL
BEI	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: End of shift at end of workweek - Notations: B, Ns
Regulatory reference	ACGIH 2021
Methanol (67-56-1)	
Belgium - Occupational Exposure Limits	
Local name	Alcool méthylique # Methanol
OEL TWA	266 mg/m ³
OEL TWA [ppm]	200 ppm
OEL STEL	333 mg/m ³
OEL STEL [ppm]	250 ppm

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
Bulgaria - Occupational Exposure Limits	
Local name	Метилов алкохол
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр.5 от 17 Януари 2020 г.)
Croatia - Occupational Exposure Limits	
Local name	Metanol
GVI (OEL TWA) [1]	260 mg/m ³
GVI (OEL TWA) [2]	200 ppm
Remark	Direktiva: 2006/15/EZ. Napomena: Koža (razvrstana kao tvar koja nadražuje kožu (H315))
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 1/2021)
Croatia - Biological limit values	
Local name	Metanol
BLV	24.7 mmol/mol Creatinine Karakteristični pokazatelj: metanol - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene 7 mg/g creatinine Karakteristični pokazatelj: metanol - Biološki uzorak: mokraća - Vrijeme uzorkovanja: na kraju radne smjene
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
Czech Republic - Occupational Exposure Limits	
Local name	Methanol (Methylalkohol)
PEL (OEL TWA)	250 mg/m ³
PEL (OEL TWA) [ppm]	188 ppm
NPK-P (OEL C)	1000 mg/m ³
NPK-P (OEL C) [ppm]	751 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Czech Republic - Biological limit values	
Local name	Methanol (Methylalkohol)
BLV	15 mg/l Ukazatel: Methanol - Biološki uzorak: moči - Doba odběru: konec směny 0.47 mmol/l Ukazatel: Methanol - Biološki uzorak: moči - Doba odběru: konec směny
Regulatory reference	Vyhláška č. 107/2013 Sb. (kterou se mění vyhláška č. 432/2003 Sb.)

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
Denmark - Occupational Exposure Limits	
Local name	Methanol (Methylalkohol)
OEL TWA [1]	260 mg/m ³
OEL TWA [2]	200 ppm
Regulatory reference	BEK nr 1426 af 28. juni 2021
Estonia - Occupational Exposure Limits	
Local name	Metanool (metüülalkohol)
OEL TWA	250 mg/m ³
OEL TWA [ppm]	200 ppm
OEL STEL	350 mg/m ³
OEL STEL [ppm]	250 ppm
Remark	A (Naha kaudu kergesti imenduv aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
Finland - Occupational Exposure Limits	
Local name	Metanoli
HTP (OEL TWA) [1]	270 mg/m ³
HTP (OEL TWA) [2]	200 ppm
HTP (OEL STEL)	330 mg/m ³
HTP (OEL STEL) [ppm]	250 ppm
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Méthanol (alcool méthylique)
VME (OEL TWA)	260 mg/m ³
VME (OEL TWA) [ppm]	200 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n°2021-434)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Methanol
AGW (OEL TWA) [1]	130 mg/m ³
AGW (OEL TWA) [2]	100 ppm
Peak exposure limitation factor	2(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); H - hautresorptiv; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
Germany - Biological limit values (TRGS 903)	
Local name	Methanol
Biological limit value	15 mg/l Parameter: Methanol - Untersuchungsmaterial: U = Urin - Probenahmezeitpunkt: b) Expositionsende, bzw. Schichtende, c) bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten - Festlegung/Begründung: 11/2019 DFG
Regulatory reference	TRGS 903
Gibraltar - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Skin
Regulatory reference	Factories (Control of Chemical Agents at Work) Regulations 2003 (LN. 2018/181)
Greece - Occupational Exposure Limits	
Local name	Μεθανόλη
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
OEL STEL	325 mg/m ³
OEL STEL [ppm]	250 ppm
Remark	Η ένδειξη «δέρμα» στις οριακές τιμές επαγγελματικής έκθεσης επισημαίνει το ενδεχόμενο σημαντικής διείσδυσης μέσω του δέρματος.
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
Local name	METANOL
AK (OEL TWA)	260 mg/m ³
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Hungary - Biological Exposure Indices	
Local name	Metanol
BEI	30 mg/l Biológiai expozíció (hatás) mutató: metanol - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén) 940 µmol/l Biológiai expozíció (hatás) mutató: metanol - Biológiai minta: vizeletben - Mintavétel ideje: m.v. (műszak végén)
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	Methanol [Methyl alcohol]
OEL TWA [1]	260 mg/m ³
OEL TWA [2]	200 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	Methanol

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
BLV	15 mg/l Parameter: methanol - Medium: urine - Sampling time: End of shift - Notations: B (Background), Ns (Non-specific)
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
Italy - Occupational Exposure Limits	
Local name	Metanolo
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Cute
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
Local name	Metanols (metilspirts, karbinols)
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Āda
Regulatory reference	Ministru kabineta 2007. gada 15. maija noteikumiem Nr. 325
Lithuania - Occupational Exposure Limits	
Local name	Metanolis (metilo alkoholis)
IPRV (OEL TWA)	260 mg/m ³
IPRV (OEL TWA) [ppm]	200 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	Méthanol
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Peau
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Malta - Occupational Exposure Limits	
Local name	Methanol
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	Skin # Ġilda
Regulatory reference	S.L.424.24 - Chemical Agents at Work Regulations (L.N.57 of 2018)
Netherlands - Occupational Exposure Limits	
Local name	Methanol
MAC-TGG (OEL TWA)	133 mg/m ³
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2021

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
Poland - Occupational Exposure Limits	
Local name	Metanol (metylowy alkohol)
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	300 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
Local name	Metanol (Álcool metílico)
OEL TWA [ppm]	200 ppm
OEL STEL [ppm]	250 ppm
Remark	P (Toxicidade percutânea); IBE (Índice biológico de exposição)
Regulatory reference	Norma Portuguesa NP 1796:2014
Portugal - Biological Exposure Indices	
Local name	Metanol
BEI	15 mg/l Parâmetro: Metanol - Meio: urina - Momento da amostragem: Fim do turno - Notação: Vb (Valor basal), Ne (Não específico)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Metanol/Alcool metilic
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
Remark	P - posibilitatea unei penetrări cutanate importante
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Romania - Biological limit values	
Local name	Alcool metilic
BLV	6 mg/l Indicator biologic: Metanol - Material biologic: urină - Momentul recoltării: sfârșit de schimb
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 584/2018)
Slovakia - Occupational Exposure Limits	
Local name	Metylalkohol (metanol)
NPHV (OEL TWA) [1]	260 mg/m ³
NPHV (OEL TWA) [2]	200 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (236/2020 Z. z.)
Slovakia - Biological limit values	
Local name	Metanol
BLV	30 µg/l Zisťovaný faktor: Metanol - Vyšetrovaný materiál: moč - Čas odberu vzorky: c) pri dlhodobej expozícii; po viacerých pracovných zmenách, b) koniec expozície alebo pracovnej zmeny
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (Zmena: 471/2011 Z.z.)
Slovenia - Occupational Exposure Limits	
Local name	metanol (metilalkohol)

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
OEL TWA	260 mg/m ³
OEL TWA [ppm]	200 ppm
OEL STEL	1040 mg/m ³
OEL STEL [ppm]	800 ppm
Remark	K (Lastnost lažjega prehajanja snovi v organizem skozi kožo), Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), BAT (Biološka mejna vrednost), EU
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Slovenia - Biological limit values	
Local name	metanol
BLV	15 mg/l Parameter: metanol - Biološki vzorec: urin - Čas vzorčenja: ob koncu delovne izmene, pri dolgotrajni izpostavljenosti: ob koncu delovne izmene po več zaporednih delavnikih
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Spain - Occupational Exposure Limits	
Local name	Metanol (Alcohol metílico)
VLA-ED (OEL TWA) [1]	266 mg/m ³
VLA-ED (OEL TWA) [2]	200 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLB® (Agente químico que tiene Valor Límite Biológico), VLI (Agente químico para el que la U.E. estableció en su día un valor Límite indicativo).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Spain - Biological limit values	
Local name	Metanol (Alcohol metílico)
BLV	15 mg/l Parámetro: Metanol - Medio: Orina - Momento de muestreo: Final de la jornada laboral - Notas: F (Fondo. El indicador está generalmente presente en cantidades detectables en personas no expuestas laboralmente. Estos niveles de fondo están considerados en el valor VLB), I (Significa que el indicador biológico es inespecífico puesto que puede encontrarse después de la exposición a otros agentes químicos)
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Sweden - Occupational Exposure Limits	
Local name	Metanol
NGV (OEL TWA)	250 mg/m ³
NGV (OEL TWA) [ppm]	200 ppm
KTV (OEL STEL)	350 mg/m ³
KTV (OEL STEL) [ppm]	250 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Methanol
WEL TWA (OEL TWA) [1]	266 mg/m ³

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methanol (67-56-1)	
WEL TWA (OEL TWA) [2]	200 ppm
WEL STEL (OEL STEL)	333 mg/m ³
WEL STEL (OEL STEL) [ppm]	250 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
USA - ACGIH - Occupational Exposure Limits	
Local name	Methanol
ACGIH OEL TWA [ppm]	200 ppm
ACGIH OEL STEL [ppm]	250 ppm
Remark (ACGIH)	TLV® Basis: Headache; eye dam; dizziness; nausea. Notations: Skin; BEI
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	METHANOL
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: End of shift - Notations: B, Ns
Regulatory reference	ACGIH 2021
Methyloxirane (75-56-9)	
EU - Biological Limit Value (BLV)	
Local name	Propylene oxide
BLV	1.3 Parameter: N-(3-hydroxypropyl) valine - Medium: blood
Regulatory reference	SCOEL List of recommended health-based BLVs and BGVs
Belgium - Occupational Exposure Limits	
Local name	Oxyde de propylène # Propyleenoxide
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Remark	C: la mention "C" signifie que l'agent en question relève du champ d'application du titre 2 relatif aux agents cancérogènes, mutagènes et reprotoïques du livre VI du code de bien-être au travail. # C: de vermelding "C" betekent dat het betrokken agens valt onder het toepassingsgebied van titel 2 betreffende kankerverwekkende, mutagene en reprotoxische agentia van boek VI van de codex over het welzijn op het werk.
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
Bulgaria - Occupational Exposure Limits	
Local name	1,2-епоксипропан
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Regulatory reference	Наредба № 10 от 26.09.2003 г. за защита на работещите от рискове, свързани с експозиция на канцерогени и мутагени при работа (изм. и доп. ДВ. бр.5 от 17 Януари 2020 г.)
Croatia - Occupational Exposure Limits	
Local name	Propilen oksid; 1,2-epoksipropan; metil-oksiran)
GVI (OEL TWA) [1]	2.4 mg/m ³

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyloxirane (75-56-9)	
GVI (OEL TWA) [2]	1 ppm
Remark	Direktiva: 2017/2398. Napomena: Karc 1B, Muta 1B
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 1/2021)
Croatia - Biological limit values	
Local name	Propilen oksid (1,2-epoksipropan)
BLV	1.3 nmol/g/hemoglobin Karakteristični pokazatelj: N-(3-hidroksipropil) valin - Biološki uzorak: krv - Vrijeme uzorkovanja: Nakon najmanje 3 mjeseca izloženosti
Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
Czech Republic - Occupational Exposure Limits	
Local name	Propylenoxid (1,2-Epoxypropan)
PEL (OEL TWA)	2.4 mg/m ³
PEL (OEL TWA) [ppm]	0.99 ppm
NPK-P (OEL C)	5 mg/m ³
NPK-P (OEL C) [ppm]	2 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
Local name	1,2-Propylenoxid (1,2-Epoxypropan; Methyloxiran)
OEL TWA [1]	2.4 mg/m ³
OEL TWA [2]	1 ppm
Regulatory reference	BEK nr 1426 af 28. juni 2021
Estonia - Occupational Exposure Limits	
Local name	Propüleenoksiid (1,2-epoksüpropan)
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	25 mg/m ³
OEL STEL [ppm]	10 ppm
Remark	C (Kantserogeenne aine)
Regulatory reference	Vabariigi Valitsuse 20. märtsi 2001. a määruse nr 105 (RT I, 17.10.2019, 2); Vabariigi Valitsuse 10. märtsi 2019. a määruse nr 84
Finland - Occupational Exposure Limits	
Local name	Propyleenioksidi (1,2-epoksipropaani)
HTP (OEL TWA) [1]	2.4 mg/m ³ (Työssä tapahtuvan altistumisen sitovat raja-arvot)
HTP (OEL TWA) [2]	1 ppm (Työssä tapahtuvan altistumisen sitovat raja-arvot)
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	1,2-Époxypropane (Oxyde de propylène)
VME (OEL TWA)	2.4 mg/m ³
VME (OEL TWA) [ppm]	1 ppm

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyloxirane (75-56-9)	
Remark	Valeurs réglementaires contraignantes; substance classée cancérogène de catégorie 1B et mutagène de catégorie 1B
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n°2021-434)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Methyloxiran (Propylenoxid)
AGW (OEL TWA) [1]	2.4 mg/m ³
AGW (OEL TWA) [2]	1 ppm
Peak exposure limitation factor	4(l)
Remark	AGS - Ausschuss für Gefahrstoffe; EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); Sh - Hautsensibilisierender Stoff; X - Krebserzeugender Stoff der Kat. 1A oder 1B oder krebserzeugende Tätigkeit oder Verfahren nach § 2 Absatz 3 Nr. 4 der Gefahrstoffverordnung – es ist zusätzlich § 10 GefStoffV zu beachten; Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; 28 - Formale Umsetzung der Richtlinie 2017/2398/EU
Regulatory reference	TRGS900
Germany - Biological limit values (TRGS 903)	
Local name	Propylenoxid (1,2-Epoxypropan)
Biological limit value	2500 pmol/g hemoglobin Parameter: N-(2-Hydroxypropyl)valin - Untersuchungsmaterial: B _E = Erythrozytenfraktion des Vollblutes - Probenahmezeitpunkt: f) nach mindestens 3 Monaten Exposition - Festlegung/Begründung: 11/2017 DFG
Regulatory reference	TRGS 903
Gibraltar - Occupational Exposure Limits	
Local name	1,2-Epoxypropane
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Regulatory reference	Factories (Control of Carcinogens and mutagens at Work) Regulations 2003 (LN. 2020/47)
Greece - Occupational Exposure Limits	
Local name	1,2-εποξυπροπάνιο [Προπυλενοξείδιο]
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Regulatory reference	Π.Δ. 26/2020 - Σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία
Hungary - Occupational Exposure Limits	
Local name	PROPILÉN-OXID (1,2-epoxipropán)
AK (OEL TWA)	2.4 mg/m ³
Regulatory reference	5/2020. (II. 6.) ITM rendelet - A kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
Ireland - Occupational Exposure Limits	
Local name	1,2-Epoxypropane [Propylene oxide]

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyloxirane (75-56-9)	
OEL TWA [1]	2.4 mg/m ³
OEL TWA [2]	1 ppm
Regulatory reference	Chemical Agents Code of Practice 2021
Ireland - Biological limit values	
Local name	Propylene Oxide
BLV	3 Parameter: N-(3-hydroxypropyl) valine - Medium: blood haemoglobin
Regulatory reference	Biological Monitoring Guidelines (HSA, 2011)
Latvia - Occupational Exposure Limits	
Local name	Propilēnoksīds (metiloksirāns, 1,2-epoksipropāns)
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Remark	Carc. 1B; Muta. 1B
Regulatory reference	Ministru kabineta 2008. gada 29. septembra noteikumi Nr. 803 (Grozījumi Ministru kabineta 2020. gada 7. janvārī noteikumiem Nr. 10).
Lithuania - Occupational Exposure Limits	
Local name	Propileno oksidas (1, 2-epoksipropanas)
IPRV (OEL TWA)	2.4 mg/m ³
IPRV (OEL TWA) [ppm]	1 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Luxembourg - Occupational Exposure Limits	
Local name	1,2-Epoxypropane
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Regulatory reference	Mémorial A N° 223 de 2021 concernant la protection des salariés contre les risques liés à l'exposition à des agents cancérogènes ou mutagènes au travail
Malta - Occupational Exposure Limits	
Local name	1,2-Epoxypropane # 1,2-Epossipropan
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Regulatory reference	S.L.424.22 - Exposure to carcinogens or mutagens at work (L.N.51 of 2021)
Netherlands - Occupational Exposure Limits	
Local name	1,2-Epoxypropan
MAC-TGG (OEL TWA)	2.4 mg/m ³
Remark	Kankerverwekkende stof
Regulatory reference	Arbeidsomstandighedenregeling 2021
Poland - Occupational Exposure Limits	
Local name	1,2-Epoksipropan (tlenek propylenu)
NDS (OEL TWA)	2.4 mg/m ³
Regulatory reference	Dz. U. 2020 poz. 61

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyloxirane (75-56-9)	
Portugal - Occupational Exposure Limits	
Local name	Óxido de propileno
OEL TWA [ppm]	2 ppm
Remark	SC (Agente com potencial para produzir sensibilização pela via cutânea); A3 (Agente carcinogénico confirmado nos animais de laboratório con relevância desconhecida no Homem)
Regulatory reference	Norma Portuguesa NP 1796:2014
Romania - Occupational Exposure Limits	
Local name	Oxid de propilenă; 1,2-Epoxipropán
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Remark	C1B - poate provoca apariția cancerului; M1B - poate provoca anomalii genetice
Regulatory reference	Hotărârea Guvernului nr. 1.218/2006 (Hotărârea nr. 53/2021)
Slovakia - Occupational Exposure Limits	
Local name	Propylénoxid (1,2-epoxypropán) (metyloxirán)
NPHV (OEL TWA) [1]	2.4 mg/m ³ (TSH)
NPHV (OEL TWA) [2]	1 ppm (TSH)
Regulatory reference	Nariadenie vlády č. 356/2006 Z. z. (235/2020 Z. z.)
Slovenia - Occupational Exposure Limits	
Local name	1,2-epoksipropán
OEL TWA	2.4 mg/m ³
OEL TWA [ppm]	1 ppm
Remark	EU, EKA (Zveza med koncentracijo rakotvornih snovi v zraku na delovnem mestu in količino snovi in/ali njenih metabolitov v organizmu)
Regulatory reference	Uradni list RS, št. 79/2019 z dne 24.12.2019
Spain - Occupational Exposure Limits	
Local name	Óxido de propileno
VLA-ED (OEL TWA) [1]	2.4 mg/m ³
VLA-ED (OEL TWA) [2]	1 ppm
Remark	C1B (Supuesto carcinógeno para el hombre), M1B (Sustancias de las que se considera que inducen mutaciones hereditarias en las células germinales humanas), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido), v (Agente cancerígeno con valor límite vinculante recogido en el anexo III del Real Decreto 665/1997 y en sus modificaciones posteriores).
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2021. INSHT
Sweden - Occupational Exposure Limits	
Local name	Propylenoxid
NGV (OEL TWA)	2.4 mg/m ³

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Methyloxirane (75-56-9)	
NGV (OEL TWA) [ppm]	1 ppm
KTV (OEL STEL)	12.5 mg/m ³
KTV (OEL STEL) [ppm]	5 ppm
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	Propylene oxide
WEL TWA (OEL TWA) [1]	2.4 mg/m ³
WEL TWA (OEL TWA) [2]	1 ppm
Remark	Carc (Capable of causing cancer and/or heritable genetic damage)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
USA - ACGIH - Occupational Exposure Limits	
Local name	Propylene oxide
ACGIH OEL TWA [ppm]	2 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: DSEN; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2021
m-Phenylenebis(methylamine) (1477-55-0)	
Belgium - Occupational Exposure Limits	
Local name	m-Xylène α, α'-diamine # m-Xyleen α, α'-diamine
OEL STEL	0.1 mg/m ³
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air, M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht, M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkprocédé moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 19/11/2020
Denmark - Occupational Exposure Limits	
Local name	m-Xylen-α,α'-diamin (α,α'-Diamino-1,3-dimethylbenzen)
OEL C	0.1 mg/m ³
OEL C [ppm]	0.02 ppm
Regulatory reference	BEK nr 1426 af 28. juni 2021
Finland - Occupational Exposure Limits	
Local name	m-Ksyleeni-alfa,alfa-diamiini

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

m-Phenylenebis(methylamine) (1477-55-0)	
OEL C	0.1 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveysministeriö)
France - Occupational Exposure Limits	
Local name	m-Xylène-α,α'-diamine
VLE (OEL C/STEL)	0.1 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Ireland - Occupational Exposure Limits	
Local name	m-Xylene α,α'-diamine (m-phenylenebis(methylamine))
OEL TWA [1]	0.1 mg/m ³
Regulatory reference	Chemical Agents Code of Practice 2021
Portugal - Occupational Exposure Limits	
Local name	m-Xileno-α,α'-diamina
OEL C [ppm]	0.1 ppm
Remark	P (Toxicidade percutânea)
Regulatory reference	Norma Portuguesa NP 1796:2014
USA - ACGIH - Occupational Exposure Limits	
Local name	m-Xylene α,α'-diamine
ACGIH OEL C [ppm]	0.018 ppm
Remark (ACGIH)	TLV® Basis: Eye, skin, & GI irr. Notations: Skin
Regulatory reference	ACGIH 2021

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Use breathing mask and filter suitable for organic gases and vapours. Safety glasses.

Personal protective equipment symbol(s):



Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Wear eye glasses with side protection according to EN 166.

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. Long-sleeved apron/clothing with liquid tight type 3, protective against liquid chemicals (tested EN 14605)

Hand protection:

EN 374. Butyl rubber. Break through time: ≥ 480 min. Layer thickness : $>1,1$ mm

8.2.2.3. Respiratory protection

Respiratory protection:

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Slight. Ammonia odour.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: > 204.4 °C
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 143.3 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Viscosity, dynamic	: $1300 - 2000$ mPa·s
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: > 1 g/cm ³
Relative vapour density at 20 °C	: 1.02
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Relative evaporation rate (water=1) : > 1

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong oxidizing agents.

10.6. Hazardous decomposition products

Carbon dioxide. Aldehydes. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

m-Phenylenebis(methylamine) (1477-55-0)	
LD50 oral rat	980 mg/kg
LD50 dermal rabbit	> 3100 mg/kg
LC50 Inhalation - Rat	1.34 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

Methyloxirane (75-56-9)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Part B - Superfast 47140

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Component

Methyloxirane (75-56-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
-------------------------	---

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
28.	Methyloxirane
29.	Methyloxirane
3(a)	Methyloxirane
3(b)	Part B - Superfast 47140 ; N,N,N',N'-Tetrakis(2-hydroxypropyl)ethylenediamine ; Methyloxirane
40.	Methyloxirane

Contains no substance on the REACH candidate list $\geq 0,1$ % / SCL

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

15.1.2. National regulations

Germany

Employment restrictions

: Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : Methyloxirane is listed
SZW-lijst van mutagene stoffen : Methyloxirane is listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Carc. 1B	Carcinogenicity, Category 1B
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 1	Flammable liquids, Category 1
H224	Extremely flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H412	Harmful to aquatic life with long lasting effects.
Muta. 1B	Germ cell mutagenicity, Category 1B
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Superfast 748-0002-088 Part B

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.